

# KM-CD1000ENK

Network Keyboard



**Features:**

- Keyboard to Control
- Standalone DVR
- Network High Speed Dome
- Network Video Server

**Connection:**

- RS485, RS422, USB, RS232 & Network

**Functions:**

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips

3-axis

USB Control

RJ-45 port

Linux

**Technical Specification**

**General**

Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485, RS422, USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1 etc
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Display	LCD, 75.2mm×33.85mm

**Environmental**

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10°C~+55°C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×160(140)mm×37.5(21)mm (W×D×H) (height: 100mm including joystick)
Weight	2.5kg (Including package)