

KX-C5011S-A

5MP Starlight HDCVI IR Bullet Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- Max 25 fps@5MP (16:9 video output)
- CVI/CVBS/AHD/TVI switchable
- 3.6 mm fixed lens (2.8 mm optional)
- Max. IR length 30m, Smart IR
- Built-in mic(-A)
- IP67, DC12V



Camera																
Image Sensor	1/2.7 inch CMOS															
Max. Resolution	2880 (H) × 1620 (V)															
Pixel	5MP															
Scanning System	Progressive															
Electronic Shutter Speed	PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s															
S/N Ratio	>65 dB															
Min. Illumination	0.01 Lux/F1.6, 30IRE, 0 Lux IR on															
Illumination Distance	30 m (98.4 ft)															
Illuminator On/Off Control	Auto; manual															
Illuminator Number	3															
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°															
Lens																
Lens Type	Fixed-focal															
Mount Type	M12															
Focal Length	2.8 mm; 3.6 mm															
Max. Aperture	F1.6															
Field of View	2.8 mm: 132° × 111° × 58° (diagonal × horizontal × vertical) 3.6 mm: 109° × 92° × 48° (diagonal × horizontal × vertical)															
Iris Type	Fixed iris															
Close Focus Distance	2.8 mm: 0.9 m (3.0 ft) 3.6 mm: 1.6 m (5.2 ft)															
DORI Distance	<table border="1"> <thead> <tr> <th>Lens</th> <th>Detect</th> <th>Observe</th> <th>Recognize</th> <th>Identify</th> </tr> </thead> <tbody> <tr> <td>2.8 mm</td> <td>63.6 m (208.7 ft)</td> <td>25.4 m (83.3 ft)</td> <td>12.7 m (41.7 ft)</td> <td>6.4 m (21.0ft)</td> </tr> <tr> <td>3.6 mm</td> <td>80 m (262.5 ft)</td> <td>32 m (105.0 ft)</td> <td>16 m (52.5 ft)</td> <td>8 m (26.2 ft)</td> </tr> </tbody> </table>	Lens	Detect	Observe	Recognize	Identify	2.8 mm	63.6 m (208.7 ft)	25.4 m (83.3 ft)	12.7 m (41.7 ft)	6.4 m (21.0ft)	3.6 mm	80 m (262.5 ft)	32 m (105.0 ft)	16 m (52.5 ft)	8 m (26.2 ft)
	Lens	Detect	Observe	Recognize	Identify											
	2.8 mm	63.6 m (208.7 ft)	25.4 m (83.3 ft)	12.7 m (41.7 ft)	6.4 m (21.0ft)											
3.6 mm	80 m (262.5 ft)	32 m (105.0 ft)	16 m (52.5 ft)	8 m (26.2 ft)												
Video																
Frame Rate	CVI: PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps															

	AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H
Resolution	5M (2880 × 1620); 4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)
Day/Night	Auto switch by ICR
BLC	BLC/HLC/DWDR
WDR	DWDR
White Balance	Auto; manual
Gain Control	Auto; manual
Noise Reduction	2D NR
Smart IR	Yes
Mirror	Off/On
Privacy Masking	Off/On (8 area, rectangle)
Port	
Audio Interface	One channel built-in mic (-A)
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Power	
Power Supply	12V ±30% DC
Power Consumption	Max 3.7W (12V DC, IR on)
Environment	
Operating Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Storage Temperature	-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)
Protection Grade	IP67
Structure	
Casing	Metal throughout the whole casing
Camera Dimensions	166.6mm×69.7mm×70.0mm (6.56"×2.75"×2.75")

KX-C5011S-A

5MP Starlight HDCVI IR Bullet Camera

Design and specifications are subject to change without notice.
Pictures in the document are for reference only, and the actual product shall prevail.

Net Weight	0.33 kg (0.73 lb)
Gross Weight	0.43 kg (0.95 lb)
Dimensions (mm[inch])	

