

## KM-CD190STNK

### Network Keyboard



- Keyboard to Control Speed Dome, NVR, IVSS, EVS, etc
- Connection RS485, RS422 (reserved), USB, RS232 & Network
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips



General	
Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485, RS422 (reserved), USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: 1 RS232/2 RS485 DVR Protocol: DH-2 SD Protocol: DH-SD1/PELCO-D/PELCO-P, etc
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Display	LCD, 75.2mm×33.85mm
Maximum Number of Users	64 (including "admin")
Max RS485 Addresses (Each User)	256
Max Number of PTZ (IPC) That Can be Added over Network (Each User)	2048
Environmental	
Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A
Power Consumption	5W
Working Temperature	-10 °C to +55 °C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×139mm×53mm (W×D×H) (height: 103mm including joystick)
Weight	1.3kg (Including package)

