

KX-CSW16G2

Packaging Dimensions

Casing Material

Installation

16-Port Unmanaged Gigabit Switch



Technical Specification Basic Layer Layer 2 Switching Capacity 32 Gbps Packet Forwarding Rate 23.808 Mpps Description of Function Port 1-14: 14 × RJ-45 10/100/1000 Mbps; Port 15-16: 2 × RJ-45 10/100/1000 Mbps (uplink) Slots Operating Temperature -10 °C to +55 °C (+14 °F to +131 °F) Operating Humidity 10%-90% (RH), non-condensing Storage Temperature -40 °C to +70 °C (-40 °F to +158 °F) Storage Humidity 5%-95% (RH), non-condensing Built in power supply: 100–240 VAC, 50/60 Hz, 0.4 A **Power Supply** Idling: 2.2 W; **Power Consumption** Full load: 7.8 W Air discharge: 8 kV; Statics Protection Contact discharge: 6 kV Common mode: 2 kV; Lightning Protection Differential mode: 0.5 kV Net Weight 0.74 kg (1.63 lb) Gross Weight 1.297 kg (2.86 lb) 294 mm × 119 mm × 44 mm (11.57" × 4.68" × 1.73") (L **Product Dimensions**

 $W \times H$)

Sheet Metal

353 mm × 215 mm × 75 mm (13.9" × 8.46" × 2.95") (L ×

Desktop mount; wall mount; rack mount

- 16 × RJ-45 10/100/1000 ports.
- · The all-gigabit ports transmit data without lag.
- · Features aggregation mode which aggregates uplink ports.
- Features isolation mode which isolates all the ports from each other
- With its solid full metal design, the device has great heat dissipation and no fan.
- · Supports rack mount, wall mount and desktop mount.













Hardware

DIP Switch	Default: Default setting
	Post isolation: Prevents traffic from being sent between
	ports 1-14, but allows ports 1-14 to send its traffic to
	the uplink ports 15-16. These uplink ports can also send
	their traffic to 1-14.
	Port aggregation: Aggregates uplink ports.

Performance

Packet Buffer Size	8.4 Mbit
Jumbo Frame	12K Byte
MAC Table Size	16K
Communication Standard	IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE 802.3ab; IEEE 802.3ad

Feature

Link Aggregation	Static link aggregation
Port Feature	IEEE 802.3x traffic control
IEEE 802.3x Flow Control	Yes

General

Packing List	1 × User Manual;
	1 × Legal and Regulatory Information;
	1 × Power Cord;
	1 × Rack-mounting Kit;



KX-CSW16G2

16-Port Unmanaged Gigabit Switch

Dimensions (mm[inch])





