

KX-CSW24G2

24-Port Unmanaged Gigabit Switch



- · 24 × RJ-45 10/100/1000 ports.
- · The all-gigabit ports transmit data without lag.
- · Features aggregation mode which aggregates uplink ports.
- Features isolation mode which isolates all the ports from each other.
- With its solid full metal design, the device has great heat dissipation and no fan.
- · Supports rack mount, wall mount and desktop mount.









IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE 802.3ab; IEEE





Basic	
Layer	Layer 2
Switching Capacity	48 Gbps
Packet Forwarding Rate	35.712 Mpps
Description of Function Slots	Port 1-22: 22 × RJ-45 10/100/1000 Mbps; Port 23-24: 2 × RJ-45 10/100/1000 Mbps (uplink)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	5%–95% (RH), non-condensing
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Humidity	5%–95% (RH), non-condensing
Power Supply	Built in power supply: 100–240 VAC, 50/60 Hz, 0.4 A
Power Consumption	Idling: 2.7 W; Full load: 12.3 W
Statics Protection	Air discharge: 8 kV; Contact discharge: 6 kV
Lightning Protection	Common mode: 2 kV; Differential mode: 0.5 kV
Net Weight	0.83 kg (1.82 lb)
Gross Weight	1.34 kg (2.95 lb)
Product Dimensions	294 mm × 119 mm × 44 mm (11.57" × 4.68" × 1.73") (L \times W × H)
Packaging Dimensions	353 mm × 215 mm × 75 mm (13.9" × 8.46" × 2.95") (L × W × H)
Casing Material	Sheet Metal
Installation	Desktop mount; wall mount; rack mount

Hardware

DIP Switch	Default: Default setting Post isolation: Prevents traffic from being sent between ports 1-22, but allows ports 1-22 to send its traffic to the uplink ports 23-24. These uplink ports can also send their traffic to 1-22. Port aggregation: Aggregates uplink ports.	
Performance		
Packet Buffer Size	8.4 Mbit	
Jumbo Frame	12K Byte	
MAC Table Size	16K	

Feature

Communication Standard

Link Aggregation	Static link aggregation
Port Feature	IEEE 802.3x traffic control
IEEE 802.3x Flow Control	Yes
General	

802.3ad

General	
Packing List 1 × User Manual;	
1 × Legal and Regulato	ory Information;
1 × Power Cord;	
$1 \times Rack$ -mounting Kit	;



KX-CSW24G2

24-Port Unmanaged Gigabit Switch

